

## TP 410 • UNS S41000 • 1.4006 • TPS-FS-4006-410

This 12% chrome steel is very deep hardening, meaning that hard martensite is formed at cooling rates as slow as 20°C/minute. The hard brittle martensites require prompt tempering at a high enough temperature to improve impact properties. Increasing nickel achieves a better combination of properties. Not very resistant to aerated seawater. Welding is limited because high preheat and immediate postweld tempering is necessary to minimize the risk of hardzone cracking. Type 410 is not equal to the austenitic steels in corrosion resistance, but satisfactorily withstands the effects of the milder acids, alkalies, fresh water and atmospheric conditions. It is the least costly of the stainless steels, containing just enough to yield stainless properties.

Material grade	Norm	Chemical composition • mass in %									
		C	Si	Mn	P	S	Cr	Ni	Mo	Ti	Sonst.
		max.	max.	max.	max.	max.	min. – max.	min. – max.	min. – max.		
1.4006	DIN 17456	0,080 - 0,150	1,00	1,00	0,045	0,030	12,00 - 14,00	0,75	-	-	-
TP410	ASME SA / ASTM A 268	0,150	1,00	1,00	0,040	0,030	11,50 - 13,50	-	-	-	-

Material grade	Norm	Mechanical properties and heat treatment					
		Rp 0,2 [MPa]	Rp 1,0 [MPa]	Rm [MPa]	A [%]	Härte	Wärmebehandlung
		min.	min.	min. – max.	min	HRB max.	
1.4006	DIN 17456	200	250	450 - 650	20	-	geglüht
TP410	ASME SA / ASTM A 268	205	-	415	20	95	geglüht

Tolerances				
AD - Rohr	AD	WD	special WT	ID
ab Ø4,550 mm	±0,050 mm	±0,150 mm	±0,100 mm	X
ab Ø9,530 mm	±0,050 mm	±0,100 mm	±0,080 mm	±0,050 mm
ab Ø30,001 mm***	±0,100 mm	±0,150 mm		±0,050 mm

\*\*\* to max. ø44,500 mm

- Tolerances acc. to DIN EN 10305-1 can be confirmed to OD 30mm
- Tolerances acc. to DIN EN ISO 1127 / DIN EN 10216-5 can be confirmed
- Tolerances acc. to ASTM can be confirmed generally

Abmessungsbereich\*

Abmessungsspektrum

AD	WD	[mm]	0,89	1,00	1,20	1,24	1,65	1,82	2,00	2,11	2,30	2,35	2,50	2,60	2,64	2,77	2,87	3,00	3,20	3,25	3,60	3,85	3,91	4,00	4,40	5,50	6,35	7,00
[mm]	[inch]	[inch]	0,035			0,048	0,065	0,072		0,083		0,093			0,104	0,109	0,113		0,126	0,128			0,154				0,250	
6,00																												
6,35	0,250																											
7,00																												
7,50																												
8,00																												
9,00																												
9,53	0,375																											
10,00																												
11,00																												
12,70	0,500																											
13,00																												
15,00																												
15,88	0,625																											
16,00																												
16,80																												
17,15	0,675																											
18,00																												
19,00																												
19,05	0,750																											
20,00																												
21,34	0,840																											
22,00																												
22,23	0,875																											
23,00																												
25,00																												
25,40	1,000																											
26,00																												
26,67	1,050																											
28,00																												
30,00																												
31,75	1,250																											
32,00																												
33,40	1,315																											
36,00																												
38,10	1,500																											
42,00																												
44,50	1,750																											

